

TECHNICAL DATA SHEET



AC+ Sanded Plywood
Coquille, OR and Riddle OR

Construction Details

Face: Selected Pine with very low average repairs

Core: Western Softwood

Centers: Western Softwood

Backs: Western Softwood

- Fully water resistant phenolic resin
- NAUF (No added Urea Formaldehyde)
- Meets APA PS 1-09 standards
- FSC Panels Available

| Panel Size | Thickness (inches) | Plys |
|------------|--------------------|--------------------------|
| 4' x 8' | 1/4, 11/32 | 3 |
| | 15/32, 19/32 | 5 |
| | 23/32 | 5 or 7 as specified (AC) |
| | 23/32 | 7 only (AA, AB) |
| | 31/32 | 7 (AC) |
| | 31/32 | 9 only (AA,AB) |

Finishing Details

- Finish Sand
- Minor Wood Putty Repair, Occasional Epoxy
- No Defects Allowed

Stamping

- AC: Back Stamp = APA Stamp
- AA/AB: End Stamp = APA Stamp

Banding and Stencil

- AC: Top Cover - Mark Thickness & Grade
- AA & AB: Top and Bottom Cover - Mark Thickness & Grade
- 3 Bands/3 Stickers

Packaging Details

| Thickness (inches) | Pieces Per Unit | #/MSF | #/Unit |
|--------------------|-----------------|-------|--------|
| 1/4 | 120 | 725 | 2,785 |
| 11/32 | 90 | 950 | 2,750 |
| 15/32 | 66 | 1,350 | 2,850 |
| 19/32 | 53 | 1,600 | 2,715 |
| 23/32 | 44 | 1,900 | 2,675 |
| 31/32 | 30 | 2,700 | 2,850 |